





Specifications

<i>Model name</i>	PCG-FX601	PCG-FX602	PCG-FX604
<i>Model number</i>	PCG-9E4M	PCG-9E3M	PCG-9E2M

<i>Operating system</i>	Microsoft® Windows® XP Home Edition	Microsoft® Windows® XP Home Edition	Microsoft® Windows® XP Home Edition
<i>Processor</i>	Mobile AMD Duron™ processor 1.1 GHz featuring PowerNow!™	Mobile AMD Duron™ processor 1.1 GHz featuring PowerNow!™	Mobile AMD Duron™ processor 1.1 GHz featuring PowerNow!™
<i>Hard disk drive</i>	20 GB	20 GB	20 GB
<i>Standard RAM</i>	256 MB SDRAM (in slot)	256 MB SDRAM (in slot)	256 MB SDRAM (in slot)
<i>Maximum RAM</i>	512 MB	512 MB	512 MB
<i>LCD screen</i>	14.1" XGA (1024x768) TFT	14.1" XGA (1024x768) TFT	15.0" XGA (1024x768) TFT
<i>L2 cache memory</i>	64 KB (on die)	64 KB (on die)	64 KB (on die)
<i>MPEG</i>	MPEG 1 Digital Video supports full-screen playback	MPEG 1 Digital Video supports full-screen playback	MPEG 1 Digital Video supports full-screen playback
<i>Graphics</i>	ATI 3D RAGE™ MOBILITY-M1 with 8 MB Video RAM and 3D accelerator	ATI 3D RAGE™ MOBILITY-M1 with 8 MB Video RAM and 3D accelerator	ATI 3D RAGE™ MOBILITY-M1 with 8 MB Video RAM and 3D accelerator
<i>Display</i>	Dual Display	Dual Display	Dual Display
<i>Sound capabilities</i>	16-bit CD-quality stereo sound	16-bit CD-quality stereo sound	16-bit CD-quality stereo sound




<i>Model name</i>	PCG-FX601	PCG-FX602	PCG-FX604
<i>Model number</i>	PCG-9E4M	PCG-9E3M	PCG-9E2M
<i>Floppy disk drive</i>	3.5" 1.44 MB (internal)	3.5" 1.44 MB (internal)	3.5" 1.44 MB (internal)
<i>CD-ROM drive DVD-ROM drive CD-RW drive</i>	<p>DVD-ROM drive: up to 24x max. CD-ROM reading speed up to 8x max. DVD-ROM reading speed</p> <p>laser diode properties: wave length: DVD 654 nm, CD 786 nm laser output: DVD 8.87 uW (max), CD 28.3 uW</p>	<p>CD-RW/DVD-ROM drive: up to 24x max. CD-ROM reading speed up to 8x max. CD-R writing speed up to 8x max. CD-RW writing speed up to 8x max. DVD-ROM reading speed</p> <p>laser diode properties: wave length: DVD 656 nm, CD 785 nm laser output: DVD 4.85 uW (max), CD 151 uW</p>	<p>CD-RW/DVD-ROM drive: up to 24x max. CD-ROM reading speed up to 8x max. CD-R writing speed up to 8x max. CD-RW writing speed up to 8x max. DVD-ROM reading speed</p> <p>laser diode properties: wave length: DVD 656 nm, CD 785 nm laser output: DVD 4.85 uW (max), CD 151 uW</p>
<i>Internal modem</i>	built-in modem V.90/K56flex (56kbps) data/fax modem	built-in modem V.90/K56flex (56kbps) data/fax modem	built-in modem V.90/K56flex (56kbps) data/fax modem
<i>Telecommunication capabilities</i>	Ethernet network, PSTN data connectivity	Ethernet network, PSTN data connectivity	Ethernet network, PSTN data connectivity
<i>Expansion capabilities</i>	two PCMCIA type II or one type III Cards and Cardbus support	two PCMCIA type II or one type III Cards and Cardbus support	two PCMCIA type II or one type III Cards and Cardbus support
<i>Built-in capabilities</i>	stereo speakers, touchpad	stereo speakers, touchpad	stereo speakers, touchpad



<i>Model name</i>	PCG-FX601	PCG-FX602	PCG-FX604
<i>Model number</i>	PCG-9E4M	PCG-9E3M	PCG-9E2M
<i>Connection capabilities on notebook</i>	port replicator, monitor (VGA output), printer, external speakers or headphone, external microphone, 2 x type II PC Card slots or 1 x type III PC Card slot, 2 USB, serial port, TV Out, modem, i.LINK™ (IEEE1394) S400, Ethernet		
<i>Supplied accessories</i>	rechargeable battery, AC adapter, AC power cord, phone cable, video cable, weight saver		
<i>Service</i>	± 1 year free VAIO-Link Service	± 1 year free VAIO-Link Service	± 1 year free VAIO-Link Service
<i>Power source</i>	19.5V DC/AC100-240V	19.5V DC/AC100-240V	19.5V DC/AC100-240V
<i>Power management</i>	ENERGY STAR® compliant ACPI (Advanced Configuration & Power Interface)	ENERGY STAR® compliant ACPI (Advanced Configuration & Power Interface)	ENERGY STAR® compliant ACPI (Advanced Configuration & Power Interface)
<i>Battery</i>	Lithium ion	Lithium ion	Lithium ion
<i>Dimensions</i>			
<i>Width</i>	324 mm	324 mm	324 mm
<i>Height</i>	35.8 mm to 46.9 mm	35.8 mm to 46.9 mm	38.5 mm to 54.1 mm
<i>Depth</i>	265.5 mm	265.5 mm	265.5 mm
<i>Weight</i>			
<i>With 1 battery and weight saver</i>	3.00 kg	3.00 kg	3.20 kg
<i>With 1 battery and floppy disk drive</i>	3.20 kg	3.20 kg	3.40 kg
<i>Operating temperature</i>	+5°C to +35°C (temperature gradient less than 10°C/hour)		

Specifications



<i>Model name</i>	PCG-FX601	PCG-FX602	PCG-FX604
<i>Model number</i>	PCG-9E4M	PCG-9E3M	PCG-9E2M

<i>Storage temperature</i>	-20°C to +60°C (temperature gradient less than 10°C/hour)
<i>Operating humidity</i>	20% to 80% (not condensed), provided that humidity is less than 65% at +35°C (hygrometer reading of less than 29°C)
<i>Storage humidity</i>	10% to 90% (not condensed), provided that humidity is less than 20% at +60°C (hygrometer reading of less than 35°C)

‡ See our special guarantee conditions.

Specifications are subject to change without notice.